


## Transient Voltage Suppressors (TVS) Data Sheet

### Features

- For surface mounted applications in order to optimize board space
- Low profile package
- Glass passivated junction
- Low inductance
- Excellent clamping capability
- 600W peak pulse power capability at 10/1000 $\mu$ s waveform, repetition rate (duty cycle): 0.01%
- Fast response time
- Typical  $I_R$  less than 1 $\mu$ A above 10V
- High Temperature soldering: 260 $^{\circ}$ C/10 seconds at terminals
- Plastic package has underwriters laboratory flammability 94V-0
- Meets MSL level 1, per J-STD-020
- AEC-Q101 qualified (Automotive grade with suffix "Q".)
- Expsemi electronics



### Mechanical Data

- Case: JEDEC SMAF. Molded plastic over glass passivated junction
- Terminal: Solder plated, solderable per MIL-STD-750, Method 2026
- Polarity: Color band denotes cathode except bi-directional models

### Applications

- AC/DC power supply
- I/O interface
- Low frequency signal transmission line

### Maximum Ratings and Characteristics

Ratings at 25 $^{\circ}$ C ambient temperature unless otherwise specified.

| Rating  | Symbol          | Value       | Units          |
|---|-----------------|-------------|----------------|
| Peak pulse power dissipation at 10/1000 $\mu$ s waveform (Note1, Note2, Fig.1)                                    | $P_{PPM}$       | Minimum 600 | Watts          |
| Peak pulse current of at 10/1000 $\mu$ s waveform (Note 1, Fig.3)   | $I_{PPM}$       | See Table   | Amps           |
| Steady state power dissipation at $T_A=50^{\circ}$ C (Fig.5)  | $P_D$           | 3.3         | Watts          |
| Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load, (JEDEC Method) (Note3, Fig.6) | $I_{FSM}$       | 40          | Amps           |
| Operating junction and Storage Temperature Range.   | $T_J, T_{STG}$  | -65 to +150 | $^{\circ}$ C   |
| Typical thermal resistance junction to lead   | $R_{\theta JL}$ | 30          | $^{\circ}$ C/W |
| Typical thermal resistance junction to ambient  | $R_{\theta JA}$ | 120         | $^{\circ}$ C/W |

Notes: 1. Non-repetitive current pulse, per Fig.3 and derated above  $T_A=25^{\circ}$ C per Fig.2.

2. Mounted on 5.0mm $\times$ 5.0mm (0.03mm thick) copper pads to each terminal.

3. 8.3ms single half sine-wave, or equivalent square wave, duty cycle=4 pulses per minutes maximum.

**Electrical Characteristics (T<sub>A</sub>=25°C)**

| Part Number    |               | Device Marking Code |     | Reverse Stand-Off Voltage | Breakdown Voltage @I <sub>T</sub> | Test Current        | Maximum Clamping Voltage @I <sub>PP</sub> | Peak Pulse Current  | Reverse Leakage @V <sub>RWM</sub> |
|----------------|---------------|---------------------|-----|---------------------------|-----------------------------------|---------------------|---|---------------------|-----------------------------------|
| Unidirectional | Bidirectional | UNI                 | BI  | V <sub>RWM</sub> (V)      | V <sub>BR</sub> (V)               | I <sub>T</sub> (mA) | V <sub>C</sub> (V)                        | I <sub>PP</sub> (A) | I <sub>R</sub> (μA)               |
| SMA6F5.0A      | SMA6F5.0CA    | FAE                 | FWE | 5.0                       | 6.40~7.00                         | 10                  | 9.2                                       | 65.3                | 800                               |
| SMA6F6.0A      | SMA6F6.0CA    | FAG                 | FWG | 6.0                       | 6.67~7.37                         | 10                  | 10.3                                      | 58.3                | 800                               |
| SMA6F6.5A      | SMA6F6.5CA    | FAK                 | FWK | 6.5                       | 7.22~7.98                         | 10                  | 11.2                                      | 53.6                | 500                               |
| SMA6F7.0A      | SMA6F7.0CA    | FAM                 | FWM | 7.0                       | 7.78~8.60                         | 10                  | 12.0                                      | 50                  | 200                               |
| SMA6F7.5A      | SMA6F7.5CA    | FAP                 | FWP | 7.5                       | 8.33~9.21                         | 1                   | 12.9                                      | 46.6                | 100                               |
| SMA6F8.0A      | SMA6F8.0CA    | FAR                 | FWR | 8.0                       | 8.89~9.83                         | 1                   | 13.6                                      | 44.2                | 50                                |
| SMA6F8.5A      | SMA6F8.5CA    | FAT                 | FWT | 8.5                       | 9.44~10.40                        | 1                   | 14.4                                      | 41.7                | 20                                |
| SMA6F9.0A      | SMA6F9.0CA    | FAV                 | FWV | 9.0                       | 10.00~11.10                       | 1                   | 15.4                                      | 39                  | 10                                |
| SMA6F10A       | SMA6F10CA     | FAX                 | FWX | 10.0                      | 11.10~12.30                       | 1                   | 17.0                                      | 35.3                | 5                                 |
| SMA6F11A       | SMA6F11CA     | FAZ                 | FWZ | 11.0                      | 12.20~13.50                       | 1                   | 18.2                                      | 33                  | 1                                 |
| SMA6F12A       | SMA6F12CA     | FBE                 | FXE | 12.0                      | 13.30~14.70                       | 1                   | 19.9                                      | 30.2                | 1                                 |
| SMA6F13A       | SMA6F13CA     | FBG                 | FXG | 13.0                      | 14.40~15.90                       | 1                   | 21.5                                      | 28                  | 1                                 |
| SMA6F14A       | SMA6F14CA     | FBK                 | FXK | 14.0                      | 15.60~17.20                       | 1                   | 23.2                                      | 25.9                | 1                                 |
| SMA6F15A       | SMA6F15CA     | FBM                 | FXM | 15.0                      | 16.70~18.50                       | 1                   | 24.4                                      | 24.6                | 1                                 |
| SMA6F16A       | SMA6F16CA     | FBP                 | FXP | 16.0                      | 17.80~19.70                       | 1                   | 26.0                                      | 23.1                | 1                                 |
| SMA6F17A       | SMA6F17CA     | FBR                 | FXR | 17.0                      | 18.90~20.90                       | 1                   | 27.6                                      | 21.8                | 1                                 |
| SMA6F18A       | SMA6F18CA     | FBT                 | FXT | 18.0                      | 20.00~22.10                       | 1                   | 29.2                                      | 20.6                | 1                                 |
| SMA6F20A       | SMA6F20CA     | FBV                 | FXV | 20.0                      | 22.20~24.50                       | 1                   | 32.4                                      | 18.6                | 1                                 |
| SMA6F22A       | SMA6F22CA     | FBX                 | FXX | 22.0                      | 24.40~26.90                       | 1                   | 35.5                                      | 17.0                | 1                                 |
| SMA6F24A       | SMA6F24CA     | FBZ                 | FXZ | 24.0                      | 26.70~29.50                       | 1                   | 38.9                                      | 15.5                | 1                                 |
| SMA6F26A       | SMA6F26CA     | FCE                 | FYE | 26.0                      | 28.90~31.90                       | 1                   | 42.1                                      | 14.3                | 1                                 |
| SMA6F28A       | SMA6F28CA     | FCG                 | FYG | 28.0                      | 31.10~34.40                       | 1                   | 45.4                                      | 13.3                | 1                                 |
| SMA6F30A       | SMA6F30CA     | FCK                 | FYK | 30.0                      | 33.30~36.80                       | 1                   | 48.4                                      | 12.4                | 1                                 |
| SMA6F33A       | SMA6F33CA     | FCM                 | FYM | 33.0                      | 36.70~40.60                       | 1                   | 53.3                                      | 11.3                | 1                                 |
| SMA6F36A       | SMA6F36CA     | FCP                 | FYP | 36.0                      | 40.00~44.20                       | 1                   | 58.1                                      | 10.4                | 1                                 |
| SMA6F40A       | SMA6F40CA     | FCR                 | FYR | 40.0                      | 44.40~49.10                       | 1                   | 64.5                                      | 9.3                 | 1                                 |
| SMA6F43A       | SMA6F43CA     | FCT                 | FYT | 43.0                      | 47.80~52.80                       | 1                   | 69.4                                      | 8.7                 | 1                                 |
| SMA6F45A       | SMA6F45CA     | FCV                 | FYV | 45.0                      | 50.00~55.30                       | 1                   | 72.7                                      | 8.3                 | 1                                 |
| SMA6F48A       | SMA6F48CA     | FCX                 | FYX | 48.0                      | 53.30~58.90                       | 1                   | 77.4                                      | 7.8                 | 1                                 |
| SMA6F51A       | SMA6F51CA     | FCZ                 | FYZ | 51.0                      | 56.70~62.70                       | 1                   | 82.4                                      | 7.3                 | 1                                 |
| SMA6F54A       | SMA6F54CA     | FRE                 | FZE | 54.0                      | 60.00~66.30                       | 1                   | 87.1                                      | 6.9                 | 1                                 |
| SMA6F58A       | SMA6F58CA     | FRG                 | FZG | 58.0                      | 64.40~71.20                       | 1                   | 93.6                                      | 6.5                 | 1                                 |
| SMA6F60A       | SMA6F60CA     | FRK                 | FZK | 60.0                      | 66.70~73.70                       | 1                   | 96.8                                      | 6.2                 | 1                                 |
| SMA6F64A       | SMA6F64CA     | FRM                 | FZM | 64.0                      | 71.10~78.60                       | 1                   | 103.0                                     | 5.9                 | 1                                 |
| SMA6F70A       | SMA6F70CA     | FRP                 | FZP | 70.0                      | 77.80~86.00                       | 1                   | 113.0                                     | 5.3                 | 1                                 |
| SMA6F75A       | SMA6F75CA     | FRR                 | FZR | 75.0                      | 83.30~92.10                       | 1                   | 121.0                                     | 5                   | 1                                 |
| SMA6F78A       | SMA6F78CA     | FRT                 | FZT | 78.0                      | 86.70~95.80                       | 1                   | 126.0                                     | 4.8                 | 1                                 |
| SMA6F85A       | SMA6F85CA     | FRV                 | FZV | 85.0                      | 94.40~104.00                      | 1                   | 137.0                                     | 4.4                 | 1                                 |
| SMA6F90A       | SMA6F90CA     | FRX                 | FZX | 90.0                      | 100.00~111.001                    |                     | 146.0                                     | 4.2                 | 1                                 |
| SMA6F100A      | SMA6F100CA    | FRZ                 | FZZ | 100.0                     | 111.00~123.00                     | 1                   | 162.0                                     | 3.8                 | 1                                 |

Ratings and Characteristic Curves ( $T_A=25^\circ\text{C}$  unless otherwise noted)

Figure 1. Peak Pulse Power Rating Curve




Figure 2. Pulse Derating Curve




Figure 3. Pulse Waveform




Figure 4. Typical Junction Capacitance




Figure 5. Steady State Power Dissipation Derating Curve





Figure 6. Maximum Non-Repetitive Forward Surge Current Uni-Directional Only




## Recommended Soldering Conditions

### Soldering Parameters

|  |                                    |                         |
|--|------------------------------------|-------------------------|
| Reflow Condition                                       |                                    | Lead-free assembly      |
| Pre Heat   | - Temperature Min ( $T_{s(min)}$ ) | 150°C                   |
|  | - Temperature Max ( $T_{s(max)}$ ) | 200°C                   |
|  | - Time (min to max) ( $t_s$ )      | 60 – 180 secs           |
| Average ramp up rate (Liquidus Temp ( $T_A$ ) to peak) |                                    | 3°C/second max          |
| $T_{s(max)}$ to $T_A$ - Ramp-up Rate                   |                                    | 3°C/second max          |
| Reflow   | - Temperature ( $T_A$ ) (Liquidus) | 217°C                   |
|  | - Time (min to max) ( $t_r$ )      | 60 – 150 seconds        |
| Peak Temperature ( $T_p$ )                             |                                    | 260 <sup>+0/-5</sup> °C |
| Time within 5°C of actual peak Temperature ( $t_p$ )   |                                    | 20 – 40 seconds         |
| Ramp-down Rate   |                                    | 6°C/second max          |
| Time 25°C to peak Temperature ( $T_p$ )                |                                    | 8 minutes Max.          |
| Do not exceed  |                                    | 260°C                   |

### Physical Specifications


|                 |  |
|-----------------|--|
| <b>Case</b>     | JEDEC SMAF Moflded Pflastic over glass passivated junction |
| <b>Polarity</b> | Color band denotes cathode except Bipolar                  |
| <b>Terminal</b> | Matte Tin-plated leads, Solderable per JESD22-B102         |



### Environmental Specifications

|                            |                          |
|----------------------------|--------------------------|
| <b>High Temp. Storage</b>  | JESD22-A103              |
| <b>HTRB</b>                | JESD22-A108              |
| <b>Temperature Cycling</b> | JESD22-A104              |
| <b>MSL</b>                 | JEDEC-J-STD-020, Level 1 |
| <b>H3TRB</b>               | JESD22-A101              |
| <b>RSH</b>                 | JESD22-A111              |

### Dimensions SMAF



SMAF

| Ref. | Dimensions  |      |        |       |
|------|-------------|------|--------|-------|
|      | Millimeters |      | Inches |       |
|      | Min.        | Max. | Min.   | Max.  |
| A    | 2.40        | 2.80 | 0.094  | 0.110 |
| B    | 3.25        | 3.70 | 0.128  | 0.146 |
| C    | 1.30        | 1.60 | 0.051  | 0.063 |
| D    | 0.55        | 1.20 | 0.022  | 0.047 |
| E    | 4.40        | 4.90 | 0.173  | 0.193 |
| F    | 0.90        | 1.40 | 0.035  | 0.055 |
| G    | 0.10        | 0.30 | 0.004  | 0.012 |

**Note:**

- Controlling dimension: in millimeters.
- General tolerance: ± 0.05mm.
- The pad layout is for reference purposes only.

