

20V N-Channel MOSFET

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)}TYP$	I_D
20V	13mΩ@10V	7A
	14mΩ@4.5V	



Feature

- Trench Technology Power MOSFET
- Low $R_{DS(ON)}$
- Low Gate Charge
- AEC-Q101 qualified (Automotive grade with suffix "Q".)

Application

- Load Switch
- DC/DC Converter

MARKING:



ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain - Source Voltage	V_{DS}	20	V
Gate - Source Voltage	V_{GS}	± 12	V
Continuous Drain Current ^{1,5}	I_D	7	A
Pulsed Drain Current ²	I_{DM}	28	A
Power Dissipation ^{4,5}	P_D	1.0	W
Thermal Resistance from Junction to Ambient ⁵	$R_{\theta JA}$	125	°C/W
Junction Temperature	T_J	150	°C
Storage Temperature	T_{STG}	-55~+150	°C







MOSFET ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Test Condition	Min	Type	Max	Unit
Off Characteristics						
Drain - Source Breakdown Voltage	$V_{(\text{BR})\text{DSS}}$	$V_{\text{GS}} = 0\text{V}, I_D = 250\mu\text{A}$	20			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{\text{DS}} = 20\text{V}, V_{\text{GS}} = 0\text{V}$			1	μA
Gate - Body Leakage Current	I_{GSS}	$V_{\text{GS}} = \pm 10\text{V}, V_{\text{DS}} = 0\text{V}$			± 100	nA
On Characteristics³						
Gate Threshold Voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{DS}} = V_{\text{GS}}, I_D = 250\mu\text{A}$	0.4	0.7	1.0	V
Drain-source On-resistance	$R_{\text{DS}(\text{on})}$	$V_{\text{GS}} = 10\text{V}, I_D = 5\text{A}$		13	17	$\text{m}\Omega$
		$V_{\text{GS}} = 4.5\text{V}, I_D = 5\text{A}$		14	21	
Dynamic Characteristics						
Input Capacitance	C_{iss}	$V_{\text{DS}} = 10\text{V}, V_{\text{GS}} = 0\text{V}, f = 1\text{MHz}$		565		pF
Output Capacitance	C_{oss}			119		
Reverse Transfer Capacitance	C_{rss}			109		
Gate Resistance	R_g	$V_{\text{DS}} = 0\text{V}, V_{\text{GS}} = 0\text{V}, f = 1\text{MHz}$		1.9		Ω
Switching Characteristics						
Total Gate Charge	Q_g	$V_{\text{DS}} = 10\text{V}, V_{\text{GS}} = 4.5\text{V}, I_D = 3.6\text{A}$		18.1		nC
Gate-source Charge	Q_{gs}			0.8		
Gate-drain Charge	Q_{gd}			3.2		
Turn-on Delay Time	$t_{d(\text{on})}$	$V_{\text{DD}} = 10\text{V}, V_{\text{GS}} = 10\text{V}, R_L = 1.7 \Omega, R_G = 3\Omega$		4		ns
Turn-on Rise Time	t_r			8		
Turn-off Delay Time	$t_{d(\text{off})}$			17		
Turn-off Fall Time	t_f			5		
Source - Drain Diode Characteristics						
Diode Forward Voltage ³	V_{SD}	$V_{\text{GS}} = 0\text{V}, I_S = 6\text{A}$			1.2	V


Notes :

1. The maximum current rating is limited by package.
2. Pulse Test : Pulse Width $\leq 10\mu\text{s}$, duty cycle $\leq 1\%$.
3. Pulse Test : Pulse Width $\leq 300\mu\text{s}$, duty cycle $\leq 2\%$.
4. The power dissipation P_D is limited by $T_{J(\text{MAX})} = 150^\circ\text{C}$.
5. Device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with $T_A = 25^\circ\text{C}$.

Typical Characteristics



SOT-23-3L Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	1.050	1.250	0.041	0.049
A1	0	0.150	0.000	0.006
A2	1.050	1.250	0.041	0.049
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	2.650	2.950	0.104	0.116
E1	1.500	1.700	0.059	0.067
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°