


SOT-363 Plastic-Encapsulate Transistors

DUAL TRANSISTOR (NPN+NPN)

FEATURES

- Epoxy meets UL 94 V-0 flammability rating
- Lead Free Finish/RoHS Compliant
- For Switching and AF Amplifier Applications
- Rugged and reliable
- AEC-Q101 qualified (Automotive grade with suffix "Q.")
- Exsemi technology

MARKING:K6N



MAXIMUM RATINGS (Ta = 25 °C)







Symbol	Parameter	Value	Units
V _{CBO}	Collector-Base Voltage	60	V
V _{CEO}	Collector-Emitter Voltage	40	V
V _{EBO}	Emitter-Base Voltage	5	V
P _c	Collector Power Dissipation	200	mW
I _c	Collector Current	200	mA
T _J	Junction Temperature	150	°C
T _{STG}	Storage Temperature	-55 to 150	°C

ELECTRICAL CHARACTERISTICS (Ta = 25 °C)



Symbol	Parameter	Test conditions	Min	Typ	Max	Unit
V _{(BR)CBO}	Collector-base breakdown voltage	I _c =10μA,I _E =0	60			V
V _{(BR)CEO}	Collector-emitter breakdown voltage	I _c =1mA,I _B =0	40			V
V _{(BR)EBO}	Emitter-base breakdown voltage	I _E =10μA,I _C =0	5			V
I _{CBO}	Collector cut-off current	V _{CB} =30V,I _E =0			50	nA
I _{EBO}	Emitter-Base Cutoff Current	V _{EB} =5V,I _C =0			50	nA
I _{CEX}	Collector cut-off current	V _{CE} =30V,V _{BE(off)} =3V			50	nA
h _{FE}	DC current gain	V _{CE} =1V,I _C =0.1mA	40			
		V _{CE} =1V,I _C =1mA	70			
		V _{CE} =1V,I _C =10mA	100		300	
		V _{CE} =1V,I _C =50mA	60			
		V _{CE} =1V,I _C =100mA	30			
V _{CE(sat)}	Collector-emitter saturation voltage	I _C =10mA,I _B =1mA			0.2	V
		I _C =50mA,I _B =5mA			0.3	V

$V_{BE(sat)}$	Base-emitter saturation voltage	$I_0=10mA, I_B=1mA$	0.65		0.85	V
		$I_0=50mA, I_B=5mA$			0.95	
f_T	Transition frequency	$V_{CE}=20V, I_C=10mA$ $f=100MHz$	300			MHZ
Cob	Collector output capacitance	$V_{CB}=5V, I_E=0$ $f=1MHz$			4	pF
NF	Noise figure	$V_{CE}=5V, I_C=0.1mA$ $f=1kHz, R_S=1K\Omega$			5	dB
t_d	Delay time	$V_{CC}=3V, V_{BE(off)}=-0.5V$ $I_C=10mA, I_{B1}=-I_{B2}=1mA$			35	nS
t_r	Rise time				35	nS
t_s	Storage time	$V_{CC}=3V, I_C=10mA$ $I_{B1}=-I_{B2}=1mA$			200	nS
t_f	Fall time				50	nS

Typical Characteristics




SOT-363 Package Outline Dimensions



SYMBOL	DIMENSIONS IN MILLIMETER	
	MIN	MAX
A	0.900	1.000
A1	0.000	0.100
A2	0.900	1.000
b	0.150	0.350
c	0.100	0.150
D	2.000	2.200
E	1.150	1.350
E1	2.150	2.400
e	0.650 TYP.	
e1	1.200	1.400
L	0.525 REF.	
L1	0.260	0.460
θ	0°	8°

SOT-363 Suggested Pad Layout



Note:

1. Controlling dimension: in millimeters.
2. General tolerance: ± 0.05 mm.
3. The pad layout is for reference purposes only.

Ordering information

Device	Package	Shipping
MMDT3904	SOT-363-6L	3000/Tape&Reel